TEMPORARY TRAFFIC CONTROL TYPICAL APPLICATION




THIS DRAWING SHALL BE USED IN COMBINATION WITH THE GENERAL NOTES AT THE BEGINNING OF STANDARDS MD 104.00.

NOTES:

DISTANCES BETWEEN VEHICLES MAY BE INCREASED OR DECREASED DEPENDING ON PAINT DRYING TIME. TERRAIN. LOCAL AREA AND OTHER FACTORS.

FOR STRIPING OPERATIONS IN THE EXTERIOR LANES. USE THE APPROPRIATE RIGHT OR LEFT ARROW ON THE ARROW PANEL. IN THIS CASE. USE THE RIGHT ARROW IF OCCUPYING LANE 1 AND THE LEFT ARROW IF OCCUPYING LANE 4.

KEY:



 ∞

ARROW PANEL





APPROVED VEHICLE SAFETY LIGHT

DIRECTION OF TRAFFIC



TRUCK MOUNTED ATTENUATOR (TMA)





10-1-01

APPROVAL 9-27-96

REVISED

REVISED

REVISED

APPROVAL 9-10-96

REVISED

REVISED

State Highway

Maryland Department of Transportation STATE HIGHWAY ADMINISTRATION

STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES

MOBILE MARKING OPERATION/EXP-FREEWAY ALL SPEEDS

STANDARD NO.

MD 104.75